



PRESENTED BY HOOSIER

TECHNICAL BULLETIN

December 29, 2025

2026 CARS Tour West Super Late Model Rule Bulletin

Effective January 1, 2026

1. The 64 1/2" spoiler approval for the Five Star ABC NEXTGEN body.
2. A minimum of 3 vertical braces is required on the rear window. Must be spaced to minimize deflection.
3. Spacer Plates cannot protrude into the intake.
4. MSD Ignition Tray is mandatory for CARS Tour West/Northwest Super Late Models (SLM) and Pro Late Models (PLM). MSD Part #6427 6CT with part #8252 Coil (Ignition Box and Coil with harness). These can be purchased at SRI Performance, QUICKCAR, and Frank's Radio. We will notify everyone as additional vendors come online.
5. Tire Spring rate testers are not allowed at any time during an event.
6. CARS TOUR WEST SUPER LATE MODEL additional engine option for 2026.

***Please Note: We will evaluate the viability of this engine package for 2027 and beyond as the 2026 season progresses.

Brodix Spec Head Engine:

Total Weight Rule: **2800 lbs.**

RPM Chip: **7600**

Only Brodix Spec Head: PN SP-CH/FO/MO. Heads must meet all specifications listed below to be legal.

- No aluminum or exotic metal engine blocks.
- All Spec heads will be supplied with CNC bowl blend and intake port matching.
- No grinding or blending of CNC work is allowed.
- No grinding or polishing of any kind is allowed anywhere on the castings.

- No use of any substance that may change or alter the shape or the size of ports or combustion chambers is allowed.
- A maximum valve size of 2.080 intake and 1.600 exhaust will be allowed for all Spec heads.
- Valve seats and guides are to remain as manufactured and in their cast positions.
- Valve angles are to remain as manufactured. The original seat center locations as provided by the head manufacturer may not be altered.
- No tapering or re-shaping of valve guides will be allowed.
- No titanium valve springs, steel only.
- Titanium valves approved.
- Cylinder heads may not be angle milled.
- The minimum combustion chamber volume will be 60 cc.
- Minimum valve stem diameter is 11/32 inches.
- Spec cylinder head serial numbers must remain on the head and may not be defaced or altered.
- No welding modifications are allowed to the original castings.
- May only be used on motors 360cid or less.

Please feel free to contact us if you
have any questions or concerns.

Chris Wright
chris@carstourwest.com
Thanks,
CARS Tour West